


Current Transducer LA 55-TP/SP27

For the electronic measurement of currents: DC, AC, pulsed..., with galvanic separation between the primary circuit and the secondary circuit.

$$I_{PN} = 50 \text{ A}$$



Electrical data

I_{PN}	Primary nominal RMS current	50	A			
I_{PM}	Primary current, measuring range	0 ... ± 100	A			
R_M	Measuring resistance @	$T_A = 70^\circ\text{C}$	$T_A = 85^\circ\text{C}$			
		$R_{M\min}$ $R_{M\max}$	$R_{M\min}$ $R_{M\max}$			
		with $\pm 12 \text{ V}$	@ $\pm 50 \text{ A}_{\max}$	0 215	0 210	Ω
		with $\pm 15 \text{ V}$	@ $\pm 100 \text{ A}_{\max}$	0 35	0 30	Ω
		@ $\pm 50 \text{ A}_{\max}$	0 335	70 330	Ω	
		@ $\pm 100 \text{ A}_{\max}$	0 95	70 90	Ω	
I_{SN}	Secondary nominal RMS current	25	mA			
N_P/N_S	Turns ratio	1 : 2000				
U_C	Supply voltage ($\pm 5\%$)	$\pm 12 \dots 15$	V			
I_C	Current consumption (± 2)	10 (@ $\pm 15 \text{ V}$) + I_S	mA			

Accuracy - Dynamic performance data

ϵ	Error @ $I_{PN}, T_A = 25^\circ\text{C}$	@ $\pm 15 \text{ V}$ ($\pm 5\%$)	± 0.65	%
		@ $\pm 12 \dots 15 \text{ V}$ ($\pm 5\%$)	± 0.90	%
ϵ_L	Linearity error		< 0.15	%
I_{OE}	Electrical offset current @ $I_p = 0, T_A = 25^\circ\text{C}$	Typ		Max
				± 0.10
I_{OM}	Magnetic offset current ¹⁾ @ $I_p = 0$ and specified R_M , after an overload of $3 \times I_{PN}$		± 0.05	± 0.15
			± 0.30	± 0.50
I_{OT}	Temperature variation of I_O	-25 $^\circ\text{C}$... +85 $^\circ\text{C}$	± 0.05	± 0.30
		-40 $^\circ\text{C}$... -25 $^\circ\text{C}$	± 0.10	± 0.50
t_{D10}	Delay time to 10 % of the final output value for I_{PN} step		< 500	ns
t_{D90}	Delay time to 90 % of the final output value for I_{PN} step ²⁾		< 1	μs
BW	Frequency bandwidth (-1 dB)		DC ... 200	kHz

General data

T_A	Ambient operating temperature	-40 ... +85	$^\circ\text{C}$
T_{Ast}	Ambient storage temperature	-40 ... +90	$^\circ\text{C}$
R_S	Resistance of secondary winding	@ $T_A = 70^\circ\text{C}$	145
		@ $T_A = 85^\circ\text{C}$	150
m	Mass	25	g
	Standards	EN 50155: 2007	
		EN 50121-3-2: 2016	
		UL 508: 2010	

Features

- Closed loop (compensated) current transducer using the Hall effect
- Insulating plastic case recognized according to UL 94-V0.

Special features

- $I_{PM} = 0 \dots \pm 100 \text{ A}$
- $N_P/N_S = 1 : 2000$
- $U_d = 3.6 \text{ kV}$ (to see page 2)
- $T_A = -40^\circ\text{C} \dots +85^\circ\text{C}$
- Potted.

Advantages

- Excellent accuracy
- Very good linearity
- Low temperature drift
- Optimized response time
- Wide frequency bandwidth
- No insertion losses
- High immunity to external interference
- Current overload capability.

Applications

- Single or three phase inverters
- Propulsion and braking choppers
- Propulsion converters
- Auxiliary converters
- Battery chargers.

Application domain

- Railway (fixed installations and onboard).

Notes: ¹⁾ Result of the coercive field of the magnetic circuit

²⁾ For a $di/dt = 100 \text{ A}/\mu\text{s}$.

Current Transducer LA 55-TP/SP27

Insulation coordination

U_d	RMS voltage for AC insulation test, 50 Hz/1 min	3.6	kV
U_{Ni}	Impulse withstand voltage 1.2/50 μ s	7.5	kV
		Min	
d_{Cp}	Creepage distance ¹⁾	8.3	mm
d_{Cl}	Clearance ²⁾	8.3	mm
CTI	Comparative tracking index (group I)	600	

Notes: ¹⁾ Distance between hole busbar and winding
²⁾ Direct distance between hole busbar and winding.

Safety

This transducer must be used in limited-energy secondary circuits according to IEC 61010-1.




This transducer must be used in electric/electronic equipment with respect to applicable standards and safety requirements in accordance with the manufacturer's operating instructions.



Caution, risk of electrical shock
 When operating the transducer, certain parts of the module can carry hazardous voltage (eg. primary busbar, power supply).
 Ignoring this warning can lead to injury and/or cause serious damage.
 This transducer is a build-in device, whose conducting parts must be inaccessible after installation.
 A protective housing or additional shield could be used.
 Main supply must be able to be disconnected.

Dimensions LA 55-TP/SP27 (in mm)



Mechanical characteristics

- General tolerance ± 0.2 mm
- Fastening & connection of primary bus bar 6.4×1.6 mm
- Recommended PCB hole 3.8 mm
- Fastening & connection of secondary 3 pins 0.6×0.7 mm
- Recommended PCB hole $\phi 1.2$ mm

Remarks

- I_s is positive when I_p flows in the direction of the arrow.
- Temperature of the primary conductor should not exceed 90 °C.
- Installation of the transducer must be done unless otherwise specified on the datasheet, according to LEM Transducer Generic Mounting Rules. Please refer to LEM document N°ANE120504 available on our Web site: <https://www.lem.com/en/file/3137/download/>.