


Current Transducer LT 10000-S

$I_{PN} = 10000 \text{ A}$

For the electronic measurement of currents : DC, AC, pulsed..., with a galvanic isolation between the primary circuit (high power) and the secondary circuit (electronic circuit).



Electrical data

I_{PN}	Primary nominal r.m.s. current	10000	A			
I_P	Primary current, measuring range (1 s/mn)	0 .. ± 15000	A			
R_M	Measuring resistance	$R_{M \min}$	$R_{M \max}$			
				with $\pm 48 \text{ V}$	@ $\pm 10000 \text{ A}_{\max}$	0
			@ $\pm 12000 \text{ A}_{\max}$	0	1	Ω
		with $\pm 60 \text{ V}$	@ $\pm 10000 \text{ A}_{\max}$	0	20	Ω
	@ $\pm 15000 \text{ A}_{\max}$	0	1.5	Ω		
I_{SN}	Secondary nominal r.m.s. current	1	A			
K_N	Conversion ratio	1 : 10000				
V_C	Supply voltage ($\pm 5 \%$)	$\pm 48 \dots 60$	V			
I_C	Current consumption	$40 (@ \pm 60 \text{ V}) + I_S$	mA			
V_d	R.m.s. voltage for AC isolation test, 50 Hz, 1 mn	$10^{1)}$	kV			
		$1^{2)}$	kV			

Features

- Closed loop (compensated) current transducer using the Hall effect
- Insulated case.

Advantages

- Excellent accuracy
- Very good linearity
- Low temperature drift
- Optimized response time
- Wide frequency bandwidth
- No insertion losses
- High immunity to external interference
- Current overload capability.

Accuracy - Dynamic performance data

X_G	Overall accuracy @ $I_{PN}, T_A = 25^\circ\text{C}$	± 0.3	%
e_L	Linearity error	< 0.1	%
I_O	Offset current @ $I_P = 0, T_A = 25^\circ\text{C}$	Typ	Max
I_{OT}	Thermal drift of I_O	± 0.6	± 1.5 mA
			± 0.8 mA
t_r	Response time ³⁾ @ 90 % of I_{PN}	< 1	μs
di/dt	di/dt accurately followed	> 50	A/ μs
f	Frequency bandwidth (-1 dB)	DC .. 100	kHz

Applications

- AC variable speed drives and servo motor drives
- Static converters for DC motor drives
- Battery supplied applications
- Uninterruptible Power Supplies (UPS)
- Switched Mode Power Supplies (SMPS)
- Power supplies for welding applications.

General data

T_A	Ambient operating temperature	- 25 .. + 70	$^\circ\text{C}$
T_S	Ambient storage temperature	- 40 .. + 85	$^\circ\text{C}$
R_S	Secondary coil resistance @ $T_A = 70^\circ\text{C}$	35	Ω
m	Mass	17	kg
	Standards	EN 50178(97.10.01)	

Notes : ¹⁾ Between primary and secondary + shield

²⁾ Between secondary and shield

³⁾ With a di/dt of 100 A/ μs .

031003/8

