


AUTOMOTIVE CURRENT TRANSDUCER OPEN LOOP TECHNOLOGY

HAH1DRW 100-S/SP5, HAH1DRW 200-S/SP5, HAH1DRW 300-S/SP5, HAH1DRW 400-S/SP5, HAH1DRW 500-S/SP5, HAH1DRW 600-S/SP5, HAH1DRW 700-S/SP5, HAH1DRW 800-S/SP5, HAH1DRW 900-S/SP5, HAH1DRW 1000-S/SP5, HAH1DRW 1100-S/SP5, HAH1DRW 1200-S/SP5, HAH1DRW 1500-S/SP5



Introduction

The HAH1DRW family for the electronic measurement of DC, AC or pulsed currents in high power and low voltage automotive applications with galvanic separation between the primary circuit (high power) and the secondary circuit (electronic circuit).

The HAH1DRW family gives you the choice of having different current measuring ranges in the same housing.

Features

- Ratiometric transducer
- Open Loop transducer using the Hall effect
- Low voltage application
- Unipolar +5 V DC power supply
- Maximum RMS primary admissible current: defined by busbar to have $T < +150\text{ }^{\circ}\text{C}$
- Operating temperature range: $-40\text{ }^{\circ}\text{C} < T < 125\text{ }^{\circ}\text{C}$
- Output voltage: full ratio-metric (in sensitivity and offset).

Special features

- Additional coating of the ASIC pins
- Compressor limiter for M4 screw.

Advantages

- Excellent accuracy
- Very good linearity
- Very low thermal offset drift
- Very low thermal sensitivity drift
- Galvanic separation
- High frequency bandwidth
- Non intrusive solution.

Automotive applications

- Electrical Power Steering
- Starter Generators
- Converters
- Battery Management
- Motor drive application.

Principle of HAH1DRW family

The open loop transducers use a Hall effect integrated circuit. The magnetic flux density B , contributing to the rise of the Hall voltage, is generated by the primary current I_p to be measured.

The current to be measured I_p is supplied by a current source i.e. battery or generator (Figure 1).

Within the linear region of the hysteresis cycle, B is proportional to:

$$B(I_p) = a \times I_p$$

The Hall voltage is thus expressed by:

$$U_{\text{Hall}} = (c_{\text{Hall}} / d) \times I_{\text{Hall}} \times a \times I_p$$

Except for I_p , all terms of this equation are constant. Therefore:

$$U_{\text{Hall}} = b \times I_p$$

a constant

b constant

c_{Hall} Hall coefficient

d thickness of the Hall plate

I_{Hall} current across the Hall plates

The measurement signal U_{Hall} amplified to supply the user output voltage or current.





Fig. 1: Principle of the open loop transducer.

Dimensions (in mm)




Mechanical characteristics

- Plastic case PBT GF 30
- Magnetic core FeSi wound core
- Mass 58 g \pm 5 %
- Pins Brass tin plated
- IP level IPx 2.

Mounting recommendation

- Connector type TYCO connector P/N 1473672-1
- Assembly torque max 2.2 N·m \pm 5 %


Electronic schematic



Remark

- $U_{out} > U_o$ when I_p flows in the positive direction (see arrow on drawing).

System architecture (example)



- $C_L < 2.2$ nF EMC protection (optional)
- RC Low pass filter (optional)

On board diagnostic

- $R_L > 10$ k Ω . Resistor for signal line diagnostic (optional)

| U_{out} | Diagnostic |
|--------------|----------------|
| Open circuit | $U_{IN} = U_C$ |
| Short GND | $U_{IN} = 0$ V |

Absolute ratings (not operating)

| Parameter | Symbol | Unit | Specification | | | Conditions |
|---|------------------|-------------------|---------------|---------|-------------|---------------------------------|
| | | | Min | Typical | Max | |
| Maximum supply voltage | $U_{C\ max}$ | V | -0.5 | | 8 | 1) |
| Ambient storage temperature | $T_{A\ st}$ | °C | -40 | | 125 | |
| Electrostatic discharge voltage (HBM) | $U_{ESD\ HBM}$ | kV | | | 8 | |
| Maximum admissible vibration (random RMS) | $\gamma_{\ max}$ | m·s ⁻² | | | 27.1 | 10 to 1000 Hz, -40 °C to 125 °C |
| RMS voltage for AC insulation test | U_d | kV | | | 2.5 | 50 Hz, 1 min |
| Creepage distance | d_{CP} | mm | 4.85 | | | |
| Clearance | d_{Cl} | mm | 4.85 | | | |
| Comparative tracking index | CTI | | PLC 3 | | | |
| Maximum output current | $I_{out\ max}$ | mA | -10 | | 10 | |
| Maximum output voltage | $U_{out\ max}$ | V | -0.5 | | $U_C + 0.5$ | |

Operating characteristics in nominal range (I_{PN})

| Parameter | Symbol | Unit | Specification | | | Conditions |
|--|-----------------|-------|---|---------|------|-----------------------------------|
| | | | Min | Typical | Max | |
| Electrical Data | | | | | | |
| Supply voltage | U_C | V | 4.75 | 5 | 5.25 | |
| Ambient operating temperature | T_A | °C | -40 | | 125 | |
| Output voltage (Analog) | U_{out} | V | $U_{out} = (U_C / 5) \times (U_o + S \times I_p)$ | | | |
| Offset voltage | U_o | V | | 2.5 | | |
| Current consumption | I_C | mA | | 20 | 25 | |
| Load resistance | R_L | KΩ | 10 | | | |
| Output internal resistance | R_{out} | Ω | | 1 | 10 | |
| Performance Data | | | | | | |
| Ratiometricity error | ε_r | % | | ±0.5 | | |
| Magnetic offset voltage | U_{OM} | mV | | ±2 | | @ $U_C = 5\ V$, @ $T_A = 25\ °C$ |
| Linearity error | ε_L | % | -1 | | 1 | % of full scale |
| Average temperature coefficient of U_{OE} | TCU_{OEAV} | mV/°C | | ±0.04 | | |
| Average temperature coefficient of S | TCS_{AV} | %/°C | | ±0.02 | | |
| Delay time to 90 % of the final output value for I_{PN} step | t_{D90} | μs | | 2 | 6 | $di/dt = 100\ A / \mu s$ |
| Frequency bandwidth | BW | kHz | 40 | | | @ -3 dB |
| Peak-to-peak noise voltage | $U_{no\ pp}$ | mV | | | 14 | DC to 1 MHz |
| Output RMS noise voltage | U_{no} | mV | | | 2.2 | |
| Phase shift | $\Delta\phi$ | ° | -4 | | | DC to 1 KHz |

Note: 1) Exceeding 6.5 V may temporarily reconfigure the device until next power on.

HAH1DRW 100-S/SP5

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|-----------|-----|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -100 | | 100 | |
| Primary nominal RMS current | I_{PN} | A | -100 | | 100 | |
| Sensitivity | S | mV/A | | 20 | | @ $T_A = 25\text{ }^\circ\text{C}$ |
| Sensitivity error | ϵ_s | % | | ± 0.6 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ± 3 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |

HAH1DRW 200-S/SP5

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|-----------|-----|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -200 | | 200 | |
| Primary nominal RMS current | I_{PN} | A | -200 | | 200 | |
| Sensitivity | S | mV/A | | 10 | | @ $T_A = 25\text{ }^\circ\text{C}$ |
| Sensitivity error | ϵ_s | % | | ± 0.6 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ± 3 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |

HAH1DRW 300-S/SP5

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|-----------|-----|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -300 | | 300 | |
| Primary nominal RMS current | I_{PN} | A | -300 | | 300 | |
| Sensitivity | S | mV/A | | 6.667 | | @ $T_A = 25\text{ }^\circ\text{C}$ |
| Sensitivity error | ϵ_s | % | | ± 0.6 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ± 3 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |

HAH1DRW 400-S/SP5

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|-----------|-----|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -400 | | 400 | |
| Primary nominal RMS current | I_{PN} | A | -400 | | 400 | |
| Sensitivity | S | mV/A | | 5 | | @ $T_A = 25\text{ }^\circ\text{C}$ |
| Sensitivity error | ϵ_s | % | | ± 0.6 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ± 3 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |

HAH1DRW 500-S/SP5

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|-----------|-----|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -500 | | 500 | |
| Primary nominal RMS current | I_{PN} | A | -500 | | 500 | |
| Sensitivity | S | mV/A | | 4 | | @ $T_A = 25\text{ }^\circ\text{C}$ |
| Sensitivity error | ϵ_s | % | | ± 0.6 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ± 3 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |

HAH1DRW 600-S/SP5

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|-----------|-----|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -600 | | 600 | |
| Primary nominal RMS current | I_{PN} | A | -600 | | 600 | |
| Sensitivity | S | mV/A | | 3.333 | | @ $T_A = 25\text{ }^\circ\text{C}$ |
| Sensitivity error | ϵ_s | % | | ± 0.6 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ± 3 | | @ $T_A = 25\text{ }^\circ\text{C}$, @ $U_C = 5\text{ V}$ |

HAH1DRW 700-S/SP5

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|---------|-----|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -700 | | 700 | |
| Primary nominal RMS current | I_{PN} | A | -700 | | 700 | |
| Sensitivity | S | mV/A | | 2.857 | | @ $T_A = 25\text{ °C}$ |
| Sensitivity error | ϵ_s | % | | ±0.6 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ±3 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |

HAH1DRW 800-S/SP5

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|---------|-----|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -800 | | 800 | |
| Primary nominal RMS current | I_{PN} | A | -800 | | 800 | |
| Sensitivity | S | mV/A | | 2.5 | | @ $T_A = 25\text{ °C}$ |
| Sensitivity error | ϵ_s | % | | ±0.6 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ±3 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |

HAH1DRW 900-S/SP5

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|---------|-----|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -900 | | 900 | |
| Primary nominal RMS current | I_{PN} | A | -900 | | 900 | |
| Sensitivity | S | mV/A | | 2.222 | | @ $T_A = 25\text{ °C}$ |
| Sensitivity error | ϵ_s | % | | ±0.6 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ±3 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |

HAH1DRW 1000-S/SP5

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|---------|------|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -1000 | | 1000 | |
| Primary nominal RMS current | I_{PN} | A | -1000 | | 1000 | |
| Sensitivity | S | mV/A | | 2 | | @ $T_A = 25\text{ °C}$ |
| Sensitivity error | ϵ_s | % | | ±0.7 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ±3 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |

HAH1DRW 1100-S/SP5


| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|---------|------|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -1100 | | 1100 | |
| Primary nominal RMS current | I_{PN} | A | -1100 | | 1100 | |
| Sensitivity | S | mV/A | | 1.818 | | @ $T_A = 25\text{ °C}$ |
| Sensitivity error | ϵ_s | % | | ±0.7 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ±3 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |

HAH1DRW 1200-S/SP5

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|---------|------|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -1200 | | 1200 | |
| Primary nominal RMS current | I_{PN} | A | -1200 | | 1200 | |
| Sensitivity | S | mV/A | | 1.67 | | @ $T_A = 25\text{ °C}$ |
| Sensitivity error | ϵ_s | % | | ±0.7 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ±3 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |

| Parameter | Symbol | Unit | Specification | | | Conditions |
|----------------------------------|--------------|------|---------------|---------|------|---|
| | | | Min | Typical | Max | |
| Performance Data | | | | | | |
| Primary current, measuring range | I_{PM} | A | -1500 | | 1500 | |
| Primary nominal RMS current | I_{PN} | A | -1500 | | 1500 | |
| Sensitivity | S | mV/A | | 1.33 | | @ $T_A = 25\text{ °C}$ |
| Sensitivity error | ϵ_s | % | | ±0.9 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |
| Electrical offset voltage | U_{OE} | mV | | ±3.6 | | @ $T_A = 25\text{ °C}$, @ $U_C = 5\text{ V}$ |


Total error ϵ_{tot}



| Total error ϵ_{tot} specification | | | | |
|--|--|--------|---|--------|
| I_P (A) | $T_A = 25\text{ °C}, U_C = 5\text{ V}$ | | $-40\text{ °C} \leq T_A \leq 125\text{ °C}, U_C = 5\text{ V}$ | |
| | $-I_{PM}$ | 45 mV | 2.25 % | 65 mV |
| 0 | 13 mV | 0.65 % | 18 mV | 0.90 % |
| I_{PM} | 45 mV | 2.25 % | 65 mV | 3.25 % |

PERFORMANCES PARAMETERS DEFINITIONS

Primary current definition:



Definition of typical, minimum and maximum values:

Minimum and maximum values for specified limiting and safety conditions have to be understood as such as values shown in "typical" graphs. On the other hand, measured values are part of a statistical distribution that can be specified by an interval with upper and lower limits and a probability for measured values to lie within this interval. Unless otherwise stated (e.g. "100 % tested"), the LEM definition for such intervals designated with "min" and "max" is that the probability for values of samples to lie in this interval is 99.73 %. For a normal (Gaussian) distribution, this corresponds to an interval between -3 sigma and +3 sigma. If "typical" values are not obviously mean or average values, those values are defined to delimit intervals with a probability of 68.27 %, corresponding to an interval between -sigma and +sigma for a normal distribution. Typical, minimum and maximum values are determined during the initial characterization of a product.

Output noise voltage:


The output voltage noise is the result of the noise floor of the Hall elements and the linear amplifier.

Magnetic offset:

The magnetic offset is the consequence of an any current on the primary side. It's defined after a stated excursion of primary current.


Linearity:

The maximum positive or negative discrepancy with a reference straight line $U_{out} = f(I_p)$.
Unit: linearity (%) expressed with full scale of I_{pN} .



Delay time t_{D90} :

The time between the primary current signal (I_{pN}) and the output signal reach at 90 % of its final value.



Sensitivity:

The transducer's sensitivity S is the slope of the straight line $U_{out} = f(I_p)$, it must establish the relation:

$$U_{out}(I_p) = U_c / 5 (S \times I_p + U_o)$$

Offset with temperature:

The error of the offset in the operating temperature is the variation of the offset in the temperature considered with the initial offset at 25 °C.

The offset variation I_{OT} is a maximum variation the offset in the temperature range:

$$I_{OT} = I_{OE \max} - I_{OE \min}$$

The offset drift $TCI_{OE \text{ AV}}$ is the I_{OT} value divided by the temperature range.

Sensitivity with temperature:

The error of the sensitivity in the operating temperature is the relative variation of sensitivity with the temperature considered with the initial offset at 25 °C.

The sensitivity variation S_T is the maximum variation (in ppm or %) of the sensitivity in the temperature range:
 $S_T = (\text{Sensitivity max} - \text{Sensitivity min}) / \text{Sensitivity at } 25 \text{ }^\circ\text{C}$.

The sensitivity drift TCS_{AV} is the S_T value divided by the temperature range. Deeper and detailed info available is our LEM technical sales offices (www.lem.com).

Offset voltage @ $I_p = 0 \text{ A}$:

The offset voltage is the output voltage when the primary current is zero. The ideal value of U_o is $U_c / 2$. So, the difference of $U_o - U_c / 2$ is called the total offset voltage error. This offset error can be attributed to the electrical offset (due to the resolution of the ASIC quiescent voltage trimming), the magnetic offset, the thermal drift and the thermal hysteresis. Deeper and detailed info available is our LEM technical sales offices (www.lem.com).

Environmental test specifications:

Refer to LEM GROUP test plan laboratory CO.11.11.515.0 with "Tracking_Test Plan_Auto" sheet.

Environmental test specifications:

Refer to LEM GROUP test plan laboratory CO.11.11.515.0 with "Tracking_Test Plan_Auto" sheet.

| Name | Standard |
|---|--|
| CHARACTERIZATION @ 25 °C (initial) | |
| Sensitivity / Accuracy / Total error | LEM 98.20.00.574.0 |
| Offset / Electrical Offset / Magnetic Offset | LEM 98.20.00.573.0 |
| Linearity error | LEM 98.20.00.370.0 |
| Current Consumption | LEM 98.20.00.579.0 |
| CHARACTERIZATION WITH T °C (initial) | |
| Sensitivity / Accuracy / Total error | LEM 98.20.00.574.0 |
| T °C variation of ... / Temperature Coefficient of G | LEM 98.20.00.574.0 |
| Offset / Electrical Offset / Magnetic Offset | LEM 98.20.00.573.0 |
| T °C variation of ... / Temperature Coefficient of Offset | LEM 98.20.00.573.0 |
| Linearity error | LEM 98.20.00.370.0 |
| Current Consumption | LEM 98.20.00.579.0 |
| ELECTRICAL TESTS @ 25 °C | |
| Phase delay check | 100 Hz to 100 KHz @ 20 A peak |
| Noise measurement | Sweep from DC to 1 MHz |
| Delay time di/dt | 100 A/ μ s. I pulse = $I_{p,max}$ |
| dv/dt | 2000 V/ μ s. U = 2000 V |
| Dielectric Withstand Voltage test | 2500 V AC / 1 min / 50 Hz |
| Insulation Resistance test | 500 V DC, time = 60 s $R_{INS} \geq 500$ M Ω Minimum |
| ENVIRONMENTAL TESTS (CLIMATIC) | |
| Thermal shock | ISO 16750-4 § 5.3.2 (04/2010) 500 cycles (500 hours), 30 min @ -40 °C // 30 min @ +125 °C U_C not connected, $I_p = 0$ |
| Steady state T °C Humidity bias life test | JESD 22-A 101 (03/2009) |
| MECHANICAL TESTS | |
| Vibration Random in T °C | ISO 16750-3 § 4.1.2.4(12/2012) 27.1 m/s ² , 8 h/axe 10 Hz -1000 Hz |
| Shocks | ISO 16750-3 § 4.2.2 (12/2012) 50 g/ 6 ms Half Sine @ 25 °C 10 shocks of each direction (Total: 60) U_C not connected, $I_p = 0$ |
| Free Fall (Device not packaged) | IEC 60068-2-31 §5.2: method 1 (05/2008) |
| EMC | |
| Immunity to ElectroStatic Discharges (Handling of devices) | ISO 10605 (07/2008) |
| Immunity to Conducted disturbances (BCI) | ISO 11452-4 (12/2011) |
| Emission Radiated (ALSE) | CISPR 25 (03/2008) |
| FINAL CHARACTERIZATION | |
| Characterization @ 25 °C | |
| Characterization with T °C | |

IMPORTANT NOTICE

The information in this document is considered accurate and reliable. However, LEM International SA and any company directly or indirectly controlled by LEM Holding SA ("LEM") do not provide any guarantee or warranty, expressed or implied, regarding the accuracy or completeness of this information and are not liable for any consequences resulting from its use. LEM shall not be responsible for any indirect, incidental, punitive, special, or consequential damages (including, but not limited to, lost profits, lost savings, business interruption, costs related to the removal or replacement of products, or rework charges) regardless of whether such damages arise from tort (including negligence), warranty, breach of contract, or any other legal theory.

LEM reserves the right to update the information in this document, including specifications and product descriptions, at any time without prior notice. Information in this document replaces any previous versions of this document. No license to any intellectual property is granted by LEM through this document, either explicitly or implicitly. Any Information and product described herein is subject to export control regulations.

LEM products may possess either unidentified or documented vulnerabilities. It is the sole responsibility of the purchaser to design and operate their applications and products in a manner that mitigates the impact of these vulnerabilities. LEM disclaims any liability for such vulnerabilities. Customers must select products with security features that best comply with applicable rules, regulations, and standards for their intended use. The purchaser is responsible for making final design decisions regarding its products and for ensuring compliance with all legal, regulatory, and security-related requirements, irrespective of any information or support provided by LEM.

LEM products are not intended, authorized, or warranted for use in life support, life-critical, or safety-critical systems or equipment, nor in applications where failure or malfunction of an LEM product could result in personal injury, death, or significant property or environmental damage. LEM and its suppliers do not assume liability for the inclusion and/or use of LEM products in such equipment or applications; thus, this inclusion and/or use is at the purchaser's own and sole risk. Unless explicitly stated that a specific LEM product is automotive qualified, it should not be used in automotive applications. LEM does not accept liability for the inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

Applications that are described herein are for illustrative purposes only. LEM makes no representation or warranty that LEM products will be suitable for a particular purpose, a specified use or application. The purchaser is solely responsible for the design and operation of its applications and devices using LEM products, and LEM accepts no liability for any assistance with any application or purchaser product design. It is purchaser's sole responsibility to determine whether the LEM product is suitable and fit for the purchaser's applications and products planned, as well as for the planned application and use of purchaser's third-party customer(s).

Stressing and using LEM products at or above limiting values will cause permanent damage to the LEM product and potentially to any device embedding or operating with LEM product. Limiting values are stress ratings only and operation of the LEM product at or above conditions and limits given in this document is not warranted. Continuous or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the LEM product.

LEM products are sold subject to the general terms and conditions of commercial sale, as published at www.lem.com unless otherwise agreed in a specific written agreement. LEM hereby expressly rejects the purchaser's general terms and conditions for purchasing LEM products by purchaser. Any terms and conditions contained in any document issued by the purchaser either before or after issuance of any document by LEM containing or referring to the general terms and conditions of sale are explicitly rejected and disregarded by LEM, and the document issued by the purchaser is wholly inapplicable to any sale or licensing made by LEM and is not binding in any way on LEM.

© 2025 LEM INTERNATIONAL SA – All rights reserved